



Junkers Magnum 250 Softpack UL Rescue System (300kg)

Product Description:

Junkers Magnum 250 Softpack UL rescue system 300kg / 150 km / h. To increase safety, every UL has a mandatory, permanently attached rescue parachute that brings the aircraft and occupants safely to earth in an emergency. The motorized paraglider and minimum flyers must also have a reserve paraglider with them, which is also firmly attached to their device.

- maximum trailer load: 300 kg
max. payload: 300 kg
- maximum speed of use: 150 km / h
max. deployment speed: 150 km / h
- Minimum usage height: 80 m
min. deployment height: 80 m
- Sink rate at max. Trailer load: 7 m / s
Descend rate in m / s with max. allowed load: 7 m / s
- Max. Opening force depending on speed and weight / max: 15 KN
deployment load depending on speed and weight / max: 15 KN
- Opening time at min./max. Load: 4.5 s at 45 km / h
opening time at min./max. speed: 4.5 s at 45 km / h
- Pack / test interval: 5 years
Revision: 5 years
- Operating time until cap change: 15 years
lifetime: 15 years
- Activation: pyrotechnic
pyrotechnic activation
- Dimensions of the standard softpack (mm): 280 x 165 x 270
Dimension softpack (mm): 280 x 165 x 270
- Weight of the entire system: 6.8 kg
total weight: 6.8 kg
- Length of the activation cord: from 0.7 m - 3.2 m in different gradations.
Length of the activations cord: 0.7 m - 3.2 m in different gradations

